

## Declaration of Performance

Annex III of regulation (EU) Nr. 305/2011



## Zemseal® PA

### No. G4C-ZemsealPA-2020-V.01

Bitumen damp proof sheet including bitumen basement tanking sheets for post application as a waterproof membrane

<b>1. Product Type:</b> Unique identification code of the product type	<b>Zemseal® PA</b> post applied waterproof membrane
<b>2. Type:</b> Batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)	<b>Zemseal® PA</b> Batch number: Refer to product label
<b>3. Intended use:</b> Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	Bitumen damp proof sheet including bitumen basement tanking sheets (EN 13969 Type A)
<b>4. Name, registered trade name:</b> Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)	<b>Zemseal® PA</b> MAX FRANK GmbH & Co. KG, Mitterweg 1, 94339 Leiblfing, Germany
<b>5. Contact address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	Not relevant (see 4)
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V	System 2+ System 3 (reaction to fire)
<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonized standard	0086 BSI Assurance UK Ltd
<b>8. Notified body (ETA):</b> In case of the declaration of performance concerning a construction product for which an ETA has been issued	-

#### Max Frank GmbH & Co. KG

Mitterweg 1 | 94339 Leiblfing | Germany | Telefon +49 9427 189-0 | Telefax +49 9427 1588 | info@maxfrank.com

---

**9. Declared performance:**

<b>Essential characteristics</b>	<b>performance</b>
Reaction to fire	Class F
Water tightness	passed
Resistance to impact (Method A)	$\geq 200$ mm
Shear resistance of joints	$\geq 200$ N/50 mm
Flexibility at low temperature	$< - 25$ °C
Tensile strength	$> 2.24$ N/mm <sup>2</sup>
Resistance to static loading	$\geq 2$ kg
Resistance to tearing	NPD
Durability after artificial aging	NPD
Chemical resistance	NPD
Hazardous substances	None

---

**10. Declaration:**

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by



.....  
Dipl.-Ing. B.Sc. Moritz Michel  
Head of Technology and Innovation

Leiblfing, 11<sup>th</sup> December 2020

---